



FITTING GUIDE

TWISTED SHOVEL

COMPATIBLE WITH ALL MAJOR MACHINE BRANDS

BOLT-ON AND LEAVE ON

AGRITUF points go the distance, which is why all our points are bolt-on.



STEP ONE

Fit the ½" bolts through to the two lower bolt holes of the twisted shovel so they feed through as shown above.



STEP TWO

Place the point on the shank, lining up the lower bolt holes with the holes on the shank.



STEP THREE

Place a washer and nut on the bolts, retaining the twisted shovel onto the shank.



STEP FOUR

Use a torque wrench to tighten both bolts to 43 foot pounds.

NOTE

Avoid over tightening with impact wrenches as this may cause the chromium blend to fracture. We recommend checking bolts for tightness after every 100 acres.

MAKE AGRITUF DO THE HARD YARDS

**BOLT THREE POINTS ONTO YOUR
MACHINE, AND PUT THEM IN
HIGH WEAR AREAS - THEN YOU'LL
SEE WHY THEY ARE THE BEST.**

- 1** Point one - in the centre
- 2** Point two - behind the wheel
- 3** Point three - outside edge

For further placement clarification refer to numbers on right image.





TWISTED SHOVEL PRODUCT CARE GUIDE

GENERAL CARE

Our superior performance is thanks to our unique chromium blend. To keep AGRITUF points performing at their peak, keep these in mind.

DON'T DROP THEM

Avoid dropping AGRITUF points on hard surfaces - our points have been designed for point first soil penetrations.

CARE WHEN LOWERING

Pay attention when lowering the machine on uneven surfaces where weight distribution onto a point(s) might cause damage.

DON'T OVER TIGHTEN

Caution when tightening with a impact gun. Do not over tighten.

MAINTAIN EQUIPMENT

While AGRITUF points go further than our competitors, they do still wear. To get the best results, make sure you're regularly checking and maintaining equipment.

EVEN TORQUE

Torque up bolts evenly with double bolt hole castings.

AGRITUF.COM



FACEBOOK.COM/AGRITUF



INSTAGRAM.COM/AGRITUF