



FITTING GUIDE

# REVERSIBLE CHISEL POINTS

COMPATIBLE WITH ALL MAJOR MACHINE BRANDS

# BOLT-ON AND LEAVE ON

AGRITUF points go the distance, which is why our points are bolt-on.



## STEP ONE

Fit the ½" bolts through the chisel point so they feed through as shown above.



## STEP TWO

Place the point on the shank with the top half of the point running up the shank.



## STEP THREE

Place a washer and nut on the bolts, retaining the chisel point onto the shank.



## STEP FOUR

Use a torque wrench to tighten both bolts to 43 foot pounds.

## NOTE

Avoid over tightening with impact wrenches as this may cause the chromium blend to fracture. We recommend checking bolts for tightness after every 100 acres.



# MAKE AGRITUF DO THE HARD YARDS

**BOLT THREE POINTS ONTO YOUR  
MACHINE, AND PUT THEM IN  
HIGH WEAR AREAS - THEN YOU'LL  
SEE WHY THEY ARE THE BEST.**

- 1** Point one - in the centre
- 2** Point two - behind the wheel
- 3** Point three - outside edge

For further placement clarification refer to numbers on right image.





# REVERSIBLE CHISEL POINT PRODUCT CARE GUIDE

## GENERAL CARE

Our superior performance is thanks to our unique chromium blend. To keep AGRITUF points performing at their peak, keep these in mind.

### DON'T DROP THEM

Avoid dropping AGRITUF points on hard surfaces - our points have been designed for point first soil penetrations.

### CARE WHEN LOWERING

Pay attention when lowering the machine on uneven surfaces where weight distribution onto a point(s) might cause damage.

### DON'T OVER TIGHTEN

Caution when tightening with a impact gun. Do not over tighten.

### MAINTAIN EQUIPMENT

While AGRITUF points go further than our competitors, they do still wear. To get the best results, make sure you're regularly checking and maintaining equipment.

### EVEN TORQUE

Torque up bolts evenly with double bolt hole castings.



**AGRITUF.COM**



**FACEBOOK.COM/AGRITUF**



**INSTAGRAM.COM/AGRITUF**