Conforms to OSHA HazCom 2012 Standard

Section 1 - Identification

Section 1 - Identification			
Product Identifier	PIRANHA TERMINATOR		
Recommended use	Floor remover.		
Recommended restrictions	For commercial and industrial use only.		
Manufacturer / Importer / Supp			
Company Name	Bio-Shine Piranha Brand		
Address	190 Summerhill Rd. Spotswood, NJ 08884		
Telephone			
Supplier Email			
Contact	888-246-7446		
Emergency Phone			
Section 2 - Hazard(s) Identification			
Physical Hazards	Not Classified		
Health Hazards	Acute toxicity, dermal	4	
	Acute toxicity, inhalation	4	
	Acute toxicity, oral	4	
	Serious eye damage/eye irritation	1	
	Skin corrosion/irritation	1 3	recontratory tract
	Specific target organ toxicity, single exposure	3	respiratory tract irritation
OSHA defined hazards Label Elements Hazard Symbol	Not Classified.		
Signal Word Hazard statement	Danger Causes severe skin burns and eye damage. Harr	nful if swall	owed, in contact with skin
	or if inhaled. May cause respiratory irritation.		
Precautionary statement	_		
Prevention	Do not breathe mist or vapor. Use only in well-ver gloves/clothing and eye/face protection. Do not ex product. Wash thoroughly after handling. Keep or	at, drink or	smoke when using this
Response	If swallowed: Rinse mouth. Do NOT induce vomit immediately all contaminated clothing. Rinse skin contaminated clothing before reuse. If inhaled: Re comfortable for breathing. Immediately call a pois cautiously with water for several minutes. Remove to do. Continue rinsing.	with water, emove pers on center/c	/shower. Wash son to fresh air and keep loctor. If in eyes: Rinse
Storage	Store locked up. Store in a well-ventilated place.	Keep cool.	
Disposal	Dispose of contents/container in accordance with regulations.	local/regio	nal/national/international
Hazard(s) not otherwise classified (HNOC)	Not classified.		

Section 3 - Composition/Information on ingredients

Mixture		
Hazardous Components		
Ingredient Name	CAS #	%
2-Amino Ethanol	141-43-5	5 - 10
2-Butoxyethanol	111-76-2	25 - 45
Composition Comments		

Conforms to OSHA HazCom 2012 Standard

ection 4 - First-aid Measures	
Inhalation	Move to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention immediately.
Skin contact	Remove contaminated clothing and shoes. Immediately flush skin with plenty of water Get prompt medical attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Check and remove contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. DO NOT induce vomiting. If victim is fully conscious, give a cupful of water. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head lower than the hips to help prevent aspiration. Call a physician or poison control center immediately.
Most Important symptoms	Causes skin and eye burns. May cause respiratory tract irritation. Symptoms may be
/effects, acute and delayed	delayed.
Indication of immediate medical	Treat symptomatically.
attention and special treatment General Information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Immediate medical attention is required. In case o shortness of breath, give oxygen. Keep victim warm.
ction 5 - Fire-fighting measures	
Suitable extinguishing media	Carbon dioxide, alcohol-resistant foam, dry chemical, water spray, or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	None known.
Special protective equipment and precautions for firefighters	Wear suitable protective equipment. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment /instruction	Move containers from fire area if you can do it without risk. Use water spray to keep fire-exposed containers cool.
General fire hazards Specific Methods	
ction 6 - Accidental release measur	es
Personal precautions, protective equipment and emergency procedures.	Isolate area. Keep unnecessary personnel away. Use personal protection as recommended in Section 8 of the SDS.
Methods and materials for containment and cleaning up	Contain spill. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Flush area with water.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
ction 7 - Handling and storage	
Precautions for safe handling	Do not get in eyes, on skin, or on clothing. Do not breathe mist or vapor. Keep container closed. Wash thoroughly after handling. Use Personal Protective Equipmer recommended in section 8 of the SDS.
Conditions for safe storage, including any incompatibilities	Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials. Keep container closed. Keep out of reach of children.
ction 8 - Exposure control/personal	protection
Occupational exposure limits	
	Air Contaminants (29 CFR 1910.1000)

03. OSHA Table 2-1 Linnis for All Containinants (23 CHX 1910.1000)			
Components	Туре	Value	
2-Amino Ethanol (CAS 141-43-5)	PEL	6 mg/m³ , 3 ppm	
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m³ , 50 ppm	
US. ACGIH Threshold Limit Values			

Conforms to OSHA HazCom 2012 Standard

	Contorms to USHA Ha	izcom zu	12 Standard
Component		Туре	Value
2-Butoxyethanol (CAS 111-76	-2)	TWA	20 ppm
2-Amino Ethanol (CAS 141-43	5-5)	STEL	6 ppm
2-Amino Ethanol (CAS 141-43	5-5)	TWA	3 ppm
US. NIOSH: Pocket Guide to C	hemical Hazards		
Components		Туре	Value
2-Amino Ethanol (CAS 141-43	3-5)	STEL	15 mg/m³, 6 ppm
2-Amino Ethanol (CAS 141-43	-	TWA	8 mg/m ³ , 3 ppm
2-Butoxyethanol (CAS 111-76		TWA	24 mg/m ³ , 5 ppm
Biological limit values	,		
US. ACGIH. BEIs. Biological E	Exposure Indices		
Component	Value		Determinate
2-Butoxyethanol (CAS 111-76	-2) 200 m	g/g	Butoxyacetic acid
		00	(BAA), with hydrolys
* - For sampling details, plea	ase see the source doo	cument.	
Exposure guidelines	Use personal protectiv	<i>le equipm</i>	ent as required. Keep working clothes separately.
US. California Code of Regulat			
Components		Exposu	
2-Butoxyethanol (CAS 111-76	-2)	-	absorbed though the
US.Minnesota Hazardous Sub			
Components		Exposu	-
2-Butoxyethanol (CAS 111-76	-2)	=	esignation applies.
US.NIOSH: Pocket Guide to Ch	,	Skin ue	signation applies.
Component	iennical nazarus	Exposu	
2-Butoxyethanol (CAS 111-76	2)	•	absorbed though the
US.OSHA Table Z-1 Limits for			
	All Containinants (29 (Exposu	-
Components 2-Butoxyethanol (CAS 111-76-2)			absorbed though the
		Can be	absorbed mough me
US.OSHA Table Z-1-A (29 CFR	1910.100)	Even	
Components		Exposu	
2-Butoxyethanol (CAS 111-76			absorbed though the
US.Tennesee. OELs Occupati	onal Exposure Limits,		
Components	2)	Exposu	
2-Butoxyethanol (CAS 111-76			absorbed though the
Appropriate engineering controls			ventilation to maintain worker exposure below ccess to water supply and eye wash facilities.
Individual protection measures, such			
Eye/face protection	Wear approved chemi and quick drench show		goggles. Provide an emergency eye wash fountain immediate work area.
Skin protection			
Hand protection	Wear chemical-resista the glove supplier.	Int, imperv	vious gloves. Suitable gloves can be recommended by
Other	Not available.		
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.		
Thermal hazards	•		ctive clothing, when necessary.
General hygiene considerations			
		5	
tion 9 - Physical and chemical prop	Clear.		
	Ultai.		
Appearance Physical state	Liquid.		

Liquid.

Form

Conforms to OSHA HazCom 2012 Standard

Color	Pale Straw.
Odor	Sassafras.
Odor threshold	Not available.
pH (Concentrate)	11.7
Melting point/freezing point	Not available.
Initial boinging point and	212 °F (100 °C)
boiling range	
Flash point	>201°F (94°C) TCC
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosiv	e limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Similar to water.
Vapor density	Similar to water.
Relative density	0.97 ± 0.01
Relative density temperature	75 °F (23.89 °C)
Solubilities	100 % Soluble.
Partition Coefficient n-	Not available
octanol/water	
Auto-ignition temperature	Not Available
Decomposition temperature	Not Available
Viscosity	< 10 cP
Viscosity Temperature	75 °F (23.89 °C)

Section 10 - Stability and reactivity

Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable at normal conditions.
Possiblity of hazardous reactio	Hazardous polymerization does not occur.
Conditions to Avoid	Keep away from heat and direct sunlight. Contact with incompatible materials.
Incompatible materials	Oxidizing agents.
Hazardous Decomposition Pro	Carbon monoxide. Carbon dioxide. Nitrogen oxides.

Section 11 - Toxicological information

Information on likely routes of expos	sure				
Ingestion	May cause burns of the gastrointestinal tract if swallowed.				
Inhalation	Irritating to respiratory system. May cause burns in mucous membranes, throat, esophagus and stomach.				
Skin contact	Causes skin burns.				
Eye contact	Causes serious eye d	Causes serious eye damage.			
Symptoms related to the physical, chemical and toxicological characteristics	Causes skin and eye burns. May cause respiratory tract irritation. Symptoms may be delayed.				
Information on toxicological effects.	S.				
Acute toxicity	Harmful if inhaled, ab	sorbed through	skin, or swa	llowed.	
Components	Level	Туре	Code	Species	Results
2-Butoxyethanol (CAS 111-76-2)	Acute	Dermal	LD50	Rabbit	400 mg/kg
	Acute	Inhalation	LC50	Rat	450 mg/l, 4 hrs
	Acute	Oral	LD50	Rat	560 mg/kg
2-Amino Ethanol (CAS 141-43-5)	Acute	Dermal	LD50	Rabbit	1025 mg/kg
	Acute	Oral	LD50	Rat	1715 mg/kg
Skin corrosion/irritation	Causes skin burns.				
Serious eye damage/ eye irritation	Causes serious eye d	lamage.			

Conforms to OSHA HazCom 2012 Standard

			Idaid
Respiratory sensitization	Not classified.		
Skin sensitization	Not classified.		
Germ cell mutagenicity	Not classified.		
Carcinogenicity		Overall Evaluation o AS 111-76-2) 3 Not c	f Carcinogenicity classifiable as to carcinogenicity to humans.
IARC Monographs. Overall Evaluation	on of Carcinogenicit	/	
Component	R	esult	Comment
2-Butoxyethanol (CAS 111-76-2)	3		Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	Not classified.		
Specific target organ toxicity - single exposure	Irritating to respirate	ory system.	
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not classified.		
Chronic effects	repeated and prolo	nged. These effects h ted exposure may ca	ugh the skin in toxic amounts if contact is have not been observed in humans. huse liver and kidney damage. These effects
Further information			
Section 12 - Ecological Information			
Ecotoxicity		ity that large or frequ	nentally hazardous. However, this does not uent spills can have a harmful or damaging
Persistence and degradability	The product is expe	cted to be biodegrad	lable.
Bioaccumulative potential	Not known.		
Partition coeficient n-octa	nol / water log (Kow)	
Components		Results	
2-Butoxyethanol (CAS 11		0.83	
2-Amino Ethanol (CAS 14	,	-1.31	
Mobility in soil	Not available.		
Mobility in general		r soluble and may sp	pread in water systems.
Other adverse effects	None known.		
Section 13 - Disposal considerations			
Disposal instructions	-		ederal, state, and local regulations.
Local disposal regulations		dance with local regu	
Hazardous waste code	product was used.		user based on the application for which the
Waste from residues / unused products		nce with all applicabl	-
Contaminated packaging	Since emptied cont container is emptied		oduct residue, follow label warnings even after
Section 14 - Transport information			
DOT	Not regulated as da		
ΙΑΤΑ	Not regulated as da		
IMDG	Not regulated as da	• •	
Transportation in bulk according to Annex II of MARPOL 73/78 and IBC Code	This substance/mix	ture is not intended to	o be transported in bulk.
General Information			
Section 15 - Regulatory Information			

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Conforms to OSHA HazCom 2012 Standard

•	CFR707, Subpt. D)	Not regulated.			
Substances (29	cifically Regulated CFR 1910.1001- dous Substance	Not on regulatory list.			
List (40 CFR 30					
		Components		Result	
		2-Butoxyethanol (CAS 111-7		LISTED	
-		orization Act of 1986 (SARA)	1		
Hazard Categories	Immediate Hazard Delayed Hazard	Yes No			
Categories	Fire Hazard	No			
	Pressure Hazard	No			
	Reactivity Hazard	No			
SARA 302 Ex substance	tremely hazardous	No			
SARA 311/31 chemical	2 Hazardous	Yes			
SARA 313 (TE			CAC #	0(h)	
-	nemical name Butoxyethanol		CAS # 111-76-2	% by wt. 25 - 45	
Other federal re	-		111-70-2	25 - 45	
	ct (CAA) Section	Not regulated.			
	ous Air Pollutants				
112(r) Acci	ct (CAA) Section dental Release (40 CFR 68.130)	Not regulated.			
	ng Water Act (SDWA)	Not regulated.			
Food and D (FDA)	Drug Administration	Not regulated.			
US state reg	ulations	California Safe Drinking Wate This material is not known to reproductive toxins.			
US.Massac	husetts RTK -	Components			
Substance	List	2-Butoxyethanol (CAS 111-7	6-2)		
		2-Amino Ethanol (CAS 141-4	-3-5)		
	rsey Worker and	Components			
Community	/ Right-to-Know Act	2-Butoxyethanol (CAS 111-7	-		
		2-Amino Ethanol (CAS 141-4	-3-5)		
	Ivania RTK -	Components			
Hazardous	Substances	2-Butoxyethanol (CAS 111-7	-		
		2-Amino Ethanol (CAS 141-4	.3-5)		
US.Rhode I	sland RTK	Components			
		2-Butoxyethanol (CAS 111-7	6-2)		
		2-Amino Ethanol (CAS 141-4	-		
	rnia Propsition 65 - ns Reproductive	Not listed.			
International In					
Country(s) or region	Inventory Name				On Inventory (yes/no)*
Australia	Australian Inven	tory of Chemical Substance	s (AICS)		Yes
Canada	Domestic Substa				Yes
Canada	Non-Domestic S	ubstances List (NDSL)			No

Conforms to OSHA HazCom 2012 Standard

China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notifed Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes
Unites States	Toxic Substances Control Act (TSCA) Inventory	Yes

Puerto Rico

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). *A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16 - Other information, including date of preparation or last version

Issue date Revision date	1/18/2015
Version #	01
Further information	
List of abbreviations	
References	
Disclaimer	The information contained herein was obtained from current and reliable sources. However, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions for use, handling, storage and disposal of this product are beyond the manufacturer's control, it is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense arising from the product's improper use. No warranty, expressed or implied, regarding the product described herein shall be created by or inferred from any statement or omission in this SDS. Various government agencies may have specific regulations concerning the transportation, handling, storage, use or disposal of this product which may not be reflected in this SDS. The user should review these regulations to ensure full compliance.